



SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

Page 1/7

Ultra-Vest, Ultra-Vest FSM, Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 1

Revision date 2015-04-06

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Ultra-Vest, Ultra-Vest FSM, Ultra-Vest(FAST), Ultra-Vest MAXX NA
Product code	Ultra-Vest Reg- FSM- FAST- MAXX NA 040615 R191

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description	Foundry material.
-------------	-------------------

1.3. Details of the supplier of the safety data sheet

Company	Ransom & Randolph
Address	3535 Briarfield Boulevard, Maumee, OH 43537 USA
Web	www.ransom-randolph.com
Telephone	+1 (419) 865-9497
Fax	+1 (419) 865-9997
Email	RR.SDS@dentsply.com
Email address of the competent person	RR.SDS@dentsply.com

1.4. Emergency telephone number


Emergency telephone number	USA +1 419 865 9497
Company	Ransom & Randolph Co. 07:30 to 16:30 (Eastern Std. / GMT minus 5)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xn; R48/20 Symbols: Xn: Harmful.
Main hazards	Harmful: danger of serious damage to health by prolonged exposure through inhalation.

2.2. Label elements

Symbols	Xn: Harmful. 
Risk phrases	R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Safety phrases	S22 - Do not breathe dust. S24/25 - Avoid contact with skin and eyes.
Precautionary Phrases	Carc. 1A: H350i - May cause cancer by inhalation. crystalline silica. Danger. Do not breathe dust.

Investment Ultra Vest
729026

Ultra-Vest, Ultra-Vest FSM, Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 1

Revision date 2015-04-06

2.2. Label elements

H372 - Causes damage to organs (lungs) through prolonged or repeated exposure .
 P202 - Do not handle until all safety precautions have been read and understood.
 P270 - Do not eat, drink or smoke when using this product.
 P285 - In case of inadequate ventilation wear respiratory protection.
 P308+P313 - IF exposed or concerned: Get medical advice/attention.
 P501 - Dispose of contents/container to local and national regulations.
 Product contains.

2.3. Other hazards

Other hazards

does not meet criteria for. PBT and vPvB assessment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Silica (cristobalite)		14464-46-1	238-455-4		40 - 70%	Xn; R48/20
Quartz		14808-60-7	238-878-4		20 - 40%	Xn; R48/20
Calcium sulfate (Plaster of Paris total inhalable dust)		26499-65-0			20 - 40%	

Further information

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash with soap and water.
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin.
Ingestion	May cause irritation to mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use extinguishing media appropriate to the surrounding fire conditions.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear suitable protective clothing.

SECTION 6: Accidental release measures

Ultra-Vest, Ultra-Vest FSM, Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 1
Revision date 2015-04-06

6.1. Personal precautions, protective equipment and emergency procedures

Avoid raising dust. Wear suitable respiratory equipment when necessary.

6.2. Environmental precautions

No environmental requirements.

6.3. Methods and material for containment and cleaning up

Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.

6.4. Reference to other sections

See section [2, 8 & 13] for further information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid raising dust. Ensure adequate ventilation of the working area. In case of insufficient ventilation, wear suitable respiratory equipment.

Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed.

7.3. Specific end use(s)

Foundry material.

SECTION 8: Exposure controls/personal protection


8.1. Control parameters

exposure limits - Crystalline Silica, Cristobalite - 0.025 mg/m³ TWA ACGIH TLV (respirable fraction); 10 mg/m³ / [2(% Silica + 2)] TWA PEL (respirable fraction).exposure limits - Crystalline Silica, quartz - 0.025 mg/m³ TWA ACGIH TLV (respirable fraction); 10 mg/m³ / (% Silica + 2) TWA PEL (respirable fraction).

8.1.1. Exposure Limit Values

Calcium sulfate (Plaster of Paris respirable dust)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m ³ : 4
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m ³ : -
Calcium sulfate (Plaster of Paris total inhalable dust)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m ³ : 10
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m ³ : -
Quartz	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m ³ : 0.3
	WEL 15 min limit ppm:	WEL 15 min limit mg/m ³ :

8.2. Exposure controls



8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Protective clothing.

Eye / face protection

In case of splashing, wear: Approved safety goggles, safety glasses with side-shields.

Ultra-Vest, Ultra-Vest FSM, Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 1

Revision date 2015-04-06

8.2. Exposure controls

Skin protection - Handprotection	Wear suitable gloves.
Respiratory protection	Suitable respiratory equipment.
8.2.3. Environmental exposure controls	Not normally required.
Occupational exposure controls	Appropriate local exhaust ventilation is required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State	Powder
Colour	Off white
Odour	Slight
pH	6 - 8
Melting point	Not applicable.
Freezing Point	Not applicable.
Boiling point	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability limits	Not applicable.
Vapour Flammability	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	2.2 - 2.7 (Water = 1 @ 20 °C)
Fat Solubility	Not applicable.
Partition coefficient	Not applicable.
Autoignition temperature	Not applicable.
Viscosity	Not applicable.
Explosive	Not applicable.
Oxidising	Not applicable.
Solubility	Slightly soluble in water

9.2. Other information

Conductivity	Not applicable.
Surface tension	Not applicable.
Gas group	Not applicable.
Benzene Content	Not applicable.
Lead content	No data available
VOC (Volatile organic compounds)	Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

	Not applicable.
--	-----------------

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	No Significant Hazard.
--	------------------------

10.5. Incompatible materials

	No Significant Hazard.
--	------------------------

Ultra-Vest,Ultra-Vest FSM,Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 1

Revision date 2015-04-06

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Harmful by inhalation.
Skin corrosion/irritation	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Respiratory or skin sensitisation	No sensitization effects reported.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	Known Human Carcinogens (Category 1).
Reproductive toxicity	No observed effect level. No observed effect concentration.
STOT-single exposure	No known adverse health effects.
STOT-repeated exposure	Chronic effects Prolonged inhalation of respirable crystalline silica In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded: "that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis." (SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003) There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).
Aspiration hazard	No Significant Hazard.
Repeated or prolonged exposure	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.

11.1.4. Toxicological Information

Ultra-Vest,Ultra-Vest FSM,Ultra-Vest(FAST), Ultra-Vest MAXX NA	Oral Mouse LD50: >5000 mg/kg
--	------------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ultra-Vest,Ultra-Vest FSM,Ultra-Vest(FAST), Ultra-Vest MAXX NA	Fish LC50/96h: 10000.000 mg/l
--	-------------------------------

12.2. Persistence and degradability

No data is available on this product.

12.3. Bioaccumulative potential

Does not bioaccumulate.

12.4. Mobility in soil

Ultra-Vest, Ultra-Vest FSM, Ultra-Vest (FAST), Ultra-Vest MAXX NA

Revision 1

Revision date 2015-04-06

12.4. Mobility in soil

Not determined.

12.5. Results of PBT and vPvB assessment

Not determined.

12.6. Other adverse effects

Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of in compliance with all, local and national regulations.

Disposal methods

Contact a licensed waste disposal company.

Disposal of packaging

Empty containers can be sent for disposal or recycling.

SECTION 14: Transport information

ADR/RID

The product is not classified as dangerous for carriage.

IMDG

The product is not classified as dangerous for carriage.

IATA

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

U.S. FEDERAL REGULATIONS:

CERCLA 103 Reportable Quantity: The Ultra-Vest (family of products) is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Chronic health

Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

U.S. STATE REGULATIONS

California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Crystalline Silica as Quartz: less than 50%, Crystalline Silica as Cristobalite: greater than 30%.

INTERNATIONAL REGULATIONS:

Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).

Ultra-Vest, Ultra-Vest FSM, Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 1

Revision date 2015-04-06

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Canadian WHMIS Classification: Class D Division 2A (Very toxic material causing other toxic effects)

European Inventory of New and Existing Chemicals Substances (EINECS): All of the components in this product are listed on the EINECS inventory.

Australian Inventory of Chemical Substances: All of the components in this product are listed on the AICS for Australia.

China Inventory of Existing Chemicals and Chemical Substances: All of the components in this product are listed on the IECSC for China.

Japanese Existing and New Chemical Substances: All of the components in this product are listed on the Japanese ENCS list.

Korean Existing Chemicals List: All of the components in this product are listed on the KECL for Korea.

Philippine Inventory of Chemicals and Chemical Substances: All of the components in this product are listed on the PICCS.

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information

Revision

This document differs from the previous version in the following areas:
15 - Precautionary Phrases.

Text of risk phrases in Section 3

R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Further information

Training
Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.